

PRODUCT NAME

Graffiti Shield ST WB Cleaner

Graffiti Cleaner

MANUFACTURER

Gemite® Products Inc.

Toll Free: 888-4-GEMITE (888-443-6483)

E-mail: techinfo@gemite.com

Web Site: www.gemite.com

USA

160-3480 East Robinson Rd.

Amherst, NY 14228

Phone 888-443-6483

Fax 888-443-6329

CANADA

1787 Drew Road

Mississauga, Ontario L5S 1J5

Phone 905-672-2020

Fax 905-672-6780

FEATURES

- Easy to use
- Highly active
- Non-regulated for transportation
- Economical
- Spray, roller or brush applied

PRODUCT DESCRIPTION

Basic Use

It is used in removal of graffiti from *Graffiti-Shield ST WB* protective coating applied to wall surfaces.

Composition and Materials

Graffiti-Shield ST WB Cleaner is in oil emulsified organic cleaner used to remove graffiti. After approximately 30-40 cleanings, the graffiti-repency of the *Graffiti-Shield ST WB* coated surface is diminished and its anti-graffiti function needs to be restored by re-coating the surface with *Graffiti-Shield ST WB*.

Limitations

Do not apply *Graffiti-Shield ST WB Cleaner* when air temperature or surface temperature are or likely to be lower than 41°F (5°C) or when rain is imminent. Some graffiti may remain on rough surfaces, even after the cleaning.

Health and Safety

Graffiti-Shield ST WB Cleaner is non-hazardous and non-regulated. If contact with skin occurs, wash with water and soap. Harmful if digested. Keep the products out of reach of children. For industrial use only. Consult MSDS for additional information.

Packaging

Graffiti-Shield ST WB Cleaner is packaged in 3.8 L (1 USG) cans or 19 L (5 USG) pails.



Coverage

Coverage of *Graffiti-Shield ST WB Cleaner* will vary considerably with the type and age of the graffiti and the surface roughness.

Storage and Transportation

Graffiti-Shield ST WB Cleaner has a shelf-life of 12 months when stored in unopened containers on pallets in a cool dry area.

GRAFFITI REMOVAL

Current Guide Specifications and Application instructions contain information specific to each application and must be followed. To remove graffiti from *Graffiti-Shield ST WB* treated substrates apply *Graffiti-Shield ST WB Cleaner* by spraying, rolling or brushing. Spraying is preferable, particularly on rough surfaces. Let the *Graffiti-Shield ST WB Cleaner* act on the graffiti for 10-15 minutes and then wash with 2,000-2,500 psi (14-17 MPa) pressure water. On rough surfaces, that may “lock in” the graffiti, or some graffiti sprays, the removal may not be complete and the procedure may have to be repeated. After approximately 30-40 graffiti removals the surface will require application of *Graffiti-Shield ST WB*.

AVAILABILITY AND COST

Graffiti-Shield ST WB Cleaner is available worldwide. Contact the manufacturer for the name of the nearest Representative/Distributor and pricing information.

WARRANTY

A limited twelve (12) month Material Replacement Warranty is available. For complete details contact Gemite’s Head Office.

TECHNICAL SERVICE

For advice on suitability of *Graffiti-Shield ST WB* for specific application, Specification assistance and application advice, contact Technical Service: USA 888-443-6483 or Canada 905-672-2020.

Short Specification

The graffiti cleaner will be *Graffiti-Shield ST WB Cleaner* manufactured by Gemite Products Inc., [USA 888-8844384 [Canada 905-672-2020]. It will meet all the Technical Data specified in the current *Graffiti-Shield ST WB Cleaner* Product Data Sheet.

Gemite Products Inc.
November 2006

9

1099623 Graffiti Resistant Coatings
1099635 Chemical Resistant Coatings