

PRODUCT NAME

Reinforcing Fabric LW™

Reinforcing Fabric Lightweight



MANUFACTURER

Gemite® Products Inc.

Toll Free: 888-4-GEMITE (888-443-6483)
E-mail: techinfo@gemite.com
Web Site: www.gemite.com

USA	CANADA
160-3480 East Robinson Rd.	1787 Drew Road
Amherst, NY 14228	Mississauga, Ontario L5S 1J5
Phone 888-443-6483	Phone 905-672-2020
Fax 888-443-6329	Fax 905-672-6780

FEATURES

- Superior Alkali Resistance
- Lightweight
- Highly Flexible
- Non-Toxic
- Non-Allergenic
- Superior Impact Strength
- Molds Easily Around Complex Shapes
- Economical

PRODUCT DESCRIPTION

Basic Use

Reinforcing Fabric LW is a stich-bonded polymeric reinforcing fabric. It is specifically designed to reinforce Flex-Top RM roof coating and Tuff-Flex CA wall coatings manufactured by Gemite Products Inc.

Composition and Materials

Reinforcing Fabric LW is made of a high quality polymeric fiber with superior durability, resistance to alkali and UV resistance.

Limitations

Reinforcing Fabric LW must not be used with Portland cement based materials. The fabric is too fine to be penetrated by cement particles.

Health and Safety

Reinforcing Fabric LW is non-toxic and non-allergenic. Keep product out of reach of children. FOR INDUSTRIAL USE ONLY. Consult MSDS for additional information.

Color

White.

Packaging

Reinforcing Fabric LW is available in rolls of 15.2 cm (6 in) and 101.6 cm (40 in) wide. The length of 40 in roll is 98.75 m (324 ft); tje length of 6 in roll is 91.44 m (300 ft) .

Yield

The actual yield will be lower than the coverage due to overlaps.

Storage and Transportation

Reinforcing Fabric LW, stored in dry and cool area, has virtually unlimited shelf life.

TECHNICAL DATA

Value	Imperial Units
Construction	Stich-bonded
Tensile Strength (ASTM D1682)	57.1 lb
Tensile Elong. (ASTM D 1682)	61-63 %
Weight	3 oz/yard ²
Color	White

INSTALLATION

Current Guide Specification and Application Instructions contain additional information specific to use of Reinforcing Fabric LW in applications of Flex-Top RD and Tuff-Flex CA products and must be followed.

AVAILABILITY AND COST

Available worldwide. Contact Gemite Products Inc. for the name of the nearest Representative/Distributor and current pricing information.

MAINTENANCE

None required.

WARRANTY

A limited twelve (12) month Material Replacement Warranty is available. For complete details contact Gemite's Head Office.

TECHNICAL SERVICE

For technical advice on suitability of Reinforcing Fabric LW for specific application, specification assistance and application advise, contact Gemite Technical Service at: USA 888-443-6483, Canada 905-672-2020.

Short Specification

The reinforcing will be Reinforcing Fabric LW manufactured by Gemite Products Inc. [USA 888-443-6483] [Canada 905-672-2020]. It shall be applied in accordance with manufacturer's current guide specifications and applications instructions. Contact Gemite Products Inc. for specification assistance and application instructions.

Gemite Products Inc.
July 1998

3

103240 Fibrous Reinforcing
Reinforcing Fabric